

Translation of the original

# Operating instruction

# Three-way ball valve

pneumatic und manual operation

Types 403x

413x

423x





PDF • ak • 03/12/2020 ENGLISH **GB** 

## KIESELMANN GmbH

Paul-Kieselmann-Str. 4-10 D - 75438 Knittlingen

Copyright: © KIESELMANN FLUID PROCESS GROUP

#### Table of contents 1.3 Personnel 4 14 1.5 2 Safety instructions 6 Intended use 6 General notes 6 3.2 Modular system 9 6.1.1 6.1.2 6.1.3 Service 13 9.2 11.1 Structure of Order Number 23

## 1 General informations

## 1.1 Informations for your safety

We are pleased that you have decided for a high-class KIESELMANN GmbH product. With correct application and adequate maintenance, our products provide long time and reliable operation.

Before installation and initiation, please carefully read this instruction manual and the security advices contained in it. This guarantees reliable and safe operation of this product and your plant respectively. Please note that an incorrect application of the process components may lead to great material damages and personal injury.

In case of damages caused by non observance of this instruction manual, incorrect initiation, handling or external interference, guarantee and warranty will lapse!

Our products are produced, mounted and tested with high diligence. However, if there is still a reason for complaint, we will naturally try to give you entire satisfaction within the scope of our warranty. We will be at your disposal also after expiration of the warranty. In addition, you will also find all necessary instructions and spare part data for maintenance in this instruction manual. If you don't want to carry out the maintenance by yourself, our KIESELMANN GmbH - service team will naturally be at your disposal.

## 1.2 Marking of security instructions

Hints are available in the chapter "safety instructions" or directly before the respective operation instruction. The hints are highlighted with a danger symbol and a signal word. Texts beside these symbols have to be read and adhered to by all means. Please continue with the text and with the handling at the valve only afterwards.

Symbol	Signal word	Meaning
<u> </u>	DANGER	Imminent danger which will result severe personal injury or death.
<u> </u>	WARNING	Imminent danger which may result severe personal injury or death.
<u> </u>	CAUTION	Dangerous situation which may cause slight personal injury or material damages.
0	NOTICE	An harmful situation which may result in damages of the product itself or of adjacent vicinity.
1	INFORMATION	Marks application hints and other information which is particularly useful.

### 1.3 General designated use

The fitting is designed exclusively for the purposes described below. Using the fitting for purposes other than those mentioned is considered contrary to its designated use. KIESELMANN GmbH cannot be held liable for any damage resulting from such use. The risk of such misuse lies entirely with the user. The prerequisite for the reliable and safe operation of the fitting is proper transportation and storage as well as competent installation and assembly. Operating the fitting within the limits of its designated use also involves observing the operating, inspection and maintenance instructions.

#### 1.4 Personnel

Personnel entrusted with the operation and maintenance of the tank safety system must have the suitable qualification to carry out their tasks. They must be informed about possible dangers and must understand and observe the safety instructions given in the relevant manual. Only allow qualified personnel to make electrical connections.

## 1.5 Modifications, spare parts, accessories

Unauthorized modifications, additions or conversions which affect the safety of the fitting are not permitted. Safety devices must not be bypassed, removed or made inactive. Only use original spare parts and accessories recommended by the manufacturer.

## 1.6 General instructions

The user is obliged to operate the fitting only when it is in good working order. In addition to the instructions given in the operating manual, please observe the relevant accident prevention regulations, generally accepted safety regulations, regulations effective in the country of installation, working and safety instructions effective in the user's plant.

## 2 Safety instructions

#### 2.1 Intended use

The Three way ball valve can be used as multiple way valve in the drinks and food industry, the pharmaceuticals and chem. Industry and the bio-technology sector.

#### 2.2 General notes



### **NOTICE - observe the operating instructions**

To avoid danger and damage, the fitting must be used in accordance with the safety instructions and technical data contained in the operating instructions.



#### **NOTICE**

All data are in line with the current state of development. Subject to change as a result of technical progress.

## 2.3 General safety instructions



### **⚠** WARNING

#### Risk of injury by outflowing medium

Dismantling the valve or valve assemblies from the plant can cause injuries.

- Medias flowing through the leakage drain outlet are to be drained off without splashing into a discharge arrangement.
- Carry the disassembling only if when the plant has been rendered pressure-less and free of liquid and gas.



## **MARNING**

#### Risk of injury by moving parts

Do not grab into the valve when the actuator is pressurized. Limbs can be crushing or amputating.

- Remove the control air line before dismantling.
- Ensure that the actuator is unpressurized.



### **⚠** WARNING

#### Risk of injury by pre-stressed pressure spring.

The pneumatic-mechanical actuator is spring-loaded. When disassembling the actuator, components that jump out may cause injuries.

- Multiturn actuator are maintenance-free and therefore do not need to be opened!



### **MARNING**

#### ATEX - Guidelines

If the valve or the plant is operated in a potentially explosive atmosphere, the valid ATEX directive of the EC and the installation instructions in this operating manual must be observed.



### **⚠** CAUTION

To avoid air leaking, only use pneumatic connection parts that have an O-ring seal facing the even surface.



#### **A** CAUTION

Before starting the system, the entire pipeline system must be thoroughly cleaned.



## **A** CAUTION

Steps should be taken to ensure that no external forces are exerted on the fitting.

## 3 Delivery, transport and storage

## 3.1 Delivery

- · Immediately after receipt check the delivery for completeness and transport damages.
- · Remove the packaging from the product.
- · Retain packaging material, or expose of according to local regulations.

#### 3.2 Transport



## **A** CAUTION

### Risk of injury and damage to the product

During the transport the generally acknowledged rules of technology, the national accident prevention regulations and company internal work and safety regulations must be observed.

### 3.3 Storage



### **NOTICE**

#### Damage to the product due to improper storage!

Observe storage instructions avoid a prolonged storage



#### **INFORMATION**

#### Recommendation for longer storage

We recommend regularly checking the product and the prevailing storage conditions during long storage times.

- · To avoid damage to seals and bearings,
  - products up to DN 125 / OD 5 inch should be stored horizontally for maximum 6 months.
  - products larger than DN 125 / 5 inch, should be stored in the upright position with the actuator on top.
- Don't store any objects on the products.
- · Protect the products for wetness, dust and dirt.
- The product should be stored in a dry and well ventilated room at a constant temperature (optimal indoor temperature: 25 C ±5; indoor humidity data 70% ±5%).
- · Protect seals, bearings and plastic parts for UV light and ozone.


## 4 Specification


## 4.1 Modular system



	drive systems				
	pneumatical		electrical		
PDA 90/75	PDA 90/100	PDA 90/125	4040		
Ø 75	Ø 100	Ø 125			








		Connection	on flanges		
S	G	K/M	FI	CI	-

## 5 Function and operation


## 5.1 Description of function

The Three way ball valve is a distribution valve with the function of the valve is the opening or closing of several pipes to divert the flow. The possible assembly-line ways in dependence of the stop functions linked with it are shown in the table as valve positions.

#### Valve positions L - ball



### Valve positions T -ball



#### Functional description for valves with manual operation

When actuating a fitting manually, the respective switching position will be locked in place in the final position. The desired valve position can be positioned in 90° steps by a rotary movement by means of a hand lever strength in a swivelling angle of 360°.

Before operation, unlock the final position lock by lifting the notch lever against the hand lever. By letting go of the notch lever in the respective final position the spring-loaded notch lever will latch back by itself to the final position lock.

#### Description of function for pneum. valves

By means of a pneum. multiturn actuator, the valve ball is rotated by a 90° rotary movement.

#### Description of function for pneum. valves

The valve opens and closes by way of a pneum. multiturn actuator with a rotary movement of 90°.

#### normal closed (NC)

• pneum. OPERATED opens the valve

not pneum. OPERATED spring force closes the valve

normal open (NO)

• pneum. OPERATED closes the valve

not pneum. OPERATED spring force opens the valve

double acting (DA)

pneum. OPERATED the valve opens or closes according to control

## 5.2 Control system and position indication

#### Retrofitting to end position feedback for manually operated valves

By replacing the hand lever and the catch disc the valve can be retrofitted for end position feedback (proximity switch).

#### Conversion from manual operation to pneumatic actuation

By a simple retrofitting operation the valve can be converted to pneumatic actuation. The rotary actuator for this purpose is supplied complete with fitting device. The following actuators are available, depending on the desired actuating function.

Nominal dia- meter	Pneum. actu- ator	air open - air close (DA)	Normally closed (NC)
DN25 - DN80 1" - 3"	PDA 90/100	4100 080 100-022	4200 080 100-022
DN 100 DN 4"	PDA 90/125	4100 100 125-022	4200 100 125-022



#### Position indicator with sensor mounting for feedback signal.

The actuator is equipped with a proximity switch mounting (sensor mounting) and a position indication. When inductive proximity initiators M 12x1 are installed, the current "Open" or "Shut" position can be interrogated. By screwing the proximity initiator to the limit position the required switching gap for the signal transmission is established.. When the valve is closed the position indication is oriented vertically to the direction of valve passage. When the valve is open it is oriented parallel to the valve passage.



## Feedback unit -optional-

Optionally, modular valve control head systems can be installed to the actuator for reading and actuating valve positions. The standard version is a closed system with SPS or ASI-bus switch-on electronics, and integrated 3/2-way solenoid valves. For tough operating conditions we recommend employing a high-grade steel cover.

## 6 Commissioning, service and maintenance

## 6.1 Commissioning

#### 6.1.1 Installation instructions

For ball valves without leakage outlet, the installation position is without importance.

Ball valves with leakage outlet must always be installed vertically to ensure that outflow of leakage, or of cleaning medium, from the valve is such that no residue will remain inside the valve.

For valves which are to be welded in on both sides, a releasable connection has to be fitted into the pipework to allow dismounting (maintenance).

#### 6.1.2 General welding guidelines

Sealing elements integrated in weld components must generally be removed prior to welding. To prevent damage, welding should be undertaken by certified personnel (EN ISO 9606-1). Use the TIG (Tungsten Inert Gas) welding process.



## **⚠** CAUTION

#### Damage and injuries due to high temperature supply

To avoid a distortion of the components, all welding parts must be welded to stress-relieved.

Allow all components to cool before assembling.



#### **NOTICE**

#### Damage due to impurities

Impurities can cause damage to the seals and seals area.

Clean inside areas prior to assembly.

#### 6.1.3 ATEX - Guidelines

For valves or plants/installations that are operated in the ATEX area, sufficient bonding (grounding) must be ensured (see valid ATEX Guidelines EG).

#### 6.2 Service



## **RECOMMENDATION**

#### Replacement of seals

To achieve optimal maintenance cycles, the following points must be observed!

- When replacement of seals, all product-contacting seals should be replaced.
- Only original spare parts may be installed.

#### Maintenance interval

The maintenance intervals depend on the operating conditions "temperature, temperature-intervals, medium, cleaning medium, pressure and opening frequency". We recommend replacing the seals 2year cycle. The user, however should establish appropriate maintenance intervals according to the condition of the seals.

#### Lubricant recommendation

EPDM; HNBR; NBR; FKM; k-flex	-	Klüber Paraliq GTE703*				
Silicone	-	Klüber Sintheso pro AA2*				
Thread	- Interflon Food*					
*) It is only permitted to use approved lubricants, if the respective fitting is used for the produc-						

tion of food or drink. Please observe the relevant safety data sheets of the manufacturers of lub ricants.

## 6.3 Cleaning

In order to ensure continuous flawless function during operation, the surfaces between the valve body and the ball must be cleaned.

Open and close the valve several times from the open position. With an angle of rotation of  $\geq 20^{\circ}$ , cleaning fluid flows into the area between the ball and casing. A time-dependent actuation in the angle of rotation range 20°-45° makes the cleaning process more efficient. The duration and the number of actuations should be adjusted according to the type of dirtying and the degree of dirtying.

## 7 Technical data

Model: Three-way ball valve

Valve size: DIN: DN 25 - DN 80

Inch: DN 1" - DN 3"

Connections: Welded end (S) DIN EN 10357

> Thread (G) DIN 11851 Flange connection (FI) Clamp connection (CI) Liner/nut (K/M) DIN11581

Temperature range: Ambient (air) +4° to +45°C

Operating (medium dependent) +0° to +95°C Sterilization (SIP 30 min)

EPDM +140°C PTFE +130°C

NBR +100°C FKM +140°C

Pressure range: Working pressure: 10 bar

> 3 bar Cleaning pressure:

A (DIN EN 12266-1) Leak rate:

Control air: Control air pressure: Quality of control air:

> 5,5 - 8,0 bar ISO 8573-1: 2001 quality class 3

Materials: Stainless steel: 1.4301 / AISI304

(in product contact) 1.4404 / AISI316L

> Surfaces: Ra < 0,8µm e-polished

Sealing material: EPDM / PTFE

> NBR / PTFE FKM / PTFE

## 8 Disassembly and assembly

### 8.1 Disassembly



### **NOTICE**

All threaded joint have right-hand thread.

Unscrew and remove control air, steam resp. cleaning lines and electrical lines, complete feedback unit or control head.

Remove the ball valve completely from the housing.

## Replacing the housing seals (3), (5), (6), (19)

- Unscrew the flange (4) (2x), (17) and (18).
- Dismantle the O-rings (5)(2x), (6)(4x), (19)(2x) and thrust collar (3)(4x).
- Remove the ball (2) out of the housing (1).

#### Replacing the sealing package (10), (11), (12)


#### **Ball valve - manual operation**

- Unscrew the screw (20) and remove the hand lever (21).
- · Unscrew the screw (16) and remove the locking disc (8).
- Remove the plain bearing (14) and the pressure spring (13) from the axis (7).
- Dismantle the axis (7) with sliding ring (9) downwards.
- Take the sealing package (10/11/12) out of the housing (1).

## Replacing the sealing package (10), (11), (12)

### Ball valve - pneum. operation

- Unscrew the screws (22) and remove the pneum. actuator (26) with the square boss (25).
- Unscrew the screws (24) and remove the angle bracket (23).
- Remove the plain bearing (14) and the pressure spring (13) from the axis (7).
- Dismantle the axis (7) with sliding ring (9) downwards.
- Take the sealing package (10/11/12) out of the housing (1).



## 8.2 Assembly

- Before installation, thoroughly clean and slightly lubricate mounting areas and running surfaces.
- · Assemble in reverse order.




### **NOTICE**

#### Instructions d'installation


Mount the sealing package (10/11/12) in the sequence shown under view.

- b) Push the bearing ring (10), the V-rings (11) (3x) and the thrust collar (12) with the mounting sleeve (M) into the limit stop.
- c) When mounting the ball (2) and the axis (7), regards for exact match from the marks on the axis (7) and the position of the ball (2).
- d) The mark points (MP) on the switch axis correspond to the respective ball openings.
- e) Mount the hand lever or the pneumatic actuator according of the valve functions.




## 9 Drawings and dimensions

## 9.1 Control units




## Position indication with sensor mounting (R)

- R1 = dog
- R1.1 = Straight pin
- R2 = Position indication
- R3 = O-ring
- R4 = Screw
- R5 = Sensor mounting
- R6 = Cap
- R7 = Screw
- LA = air supply




## 9.2 Drawings


· Example: Ball valve, T-ball with male part flange




## **Exploded drawing**



## 9.3 Dimensions





DN	d1	d2	d3	d4	d5	dLK	L1	L2	L3	L4	L5	L6	L7	L8	d∎
25	26	Rd52x1/6	104	50.5	80	65	303	118	64	75	74.5	77	165	180	10
1"	22.1			50.5											
32	32	Rd58x1/6	104	50.5	86	71	314	124	70	84	80.5	83	165	180	10
-	-			50.5											
40	38	Rd65x1/6	104	50.5	92	77	319	129	80	95	90.5	93	165	180	10
1½"	34.8			50.5											
50	50	Rd78x1/6	104	64	108	92	328	138	85	103	96.5	99	165	180	10
2"	47.5			64											
65	66	Rd95x1/6	104	91	130	110	342	152	100	122	118	114	165	180	10
2½"	60.2			77.5							-				
80	81	Rd110x1/4	129	106	146	126	401	194	115	141	132	128	-	285	14
3"	72.1			91							149				

## 10 Wearing parts

## 10.1 Wear parts kit

## Sealing kit

· Pos. (3), (5), (6), (9), (10), (11), (12), (14), (19), (M)

DN	NBR/PTFE	EPDM/PTFE	VITON/PTFE	- Mounting sleeve* M
25	4085 025 000-000	4085 025 000-054	4085 025 000-051	4084 080 021-057
1"				
32	4085 032 000-000	4085 032 000-054	4085 032 000-051	4084 080 021-057
-				
40	4085 040 000-000	4085 040 000-054	4085 040 000-051	4084 080 021-057
1½"				
50	4085 050 000-000	4085 050 000-054	4085 050 000-051	4084 080 021-057
2"				
65	4085 065 000-000	4085 065 000-054	4085 065 000-051	4084 080 021-057
21/2"				
80	4085 080 000-000	4085 080 000-054	4085 080 000-051	4084 100 021-057
3"				


<sup>\*)</sup> not included in seal kit

## 10.2 Spare parts list

Pos.	Designation	Material:
1	Housing	1.4301, 1.4404
2	ball	1.4301, 1.4404
3a	Thrust collar	PTFE
3b	Filling element optional	PTFE
4	Flanges:	1.4301, 1.4404
	Male (G)	
	- Small flange (FI)	
	Liner/nut (K/M)	
	Clamp (Cl)	
5	O-ring	- NBR, EPDM, FKM
6	O-ring	- NBR, EPDM, FKM
7	axis	1.4301, 1.4404
8	locking disc	1.4308
9	sliding ring	PTFE
10	Backup ring	PTFE
11	V-ring package	PTFE
12	Thrust collar	PTFE
13	Compression spring	1.4310
14	Plain bearing	PTFE
15	Straight pin DIN7	1.4301
16	Socket screw DIN912	1.4301
17	Blind flange	1.4301, 1.4404
18	Flanges:	1.4301, 1.4404
	Male (G)	
	- Small flange (FI)	
	Liner/nut (K/M)	
	Clamp (CI)	
19	O-ring	- NBR, EPDM, FKM
20a	saucer-head screw	1.4301
20b	Socket screw DIN912	1.4301
21a	Hand lever - GFK	GFK
21b	Hand lever - stainless steel	1.4301
22	Socket screw DIN912	1.4301
23	Holding flange	1.4301
24	Socket screw DIN912	1.4301
25	Square boss	1.4301
26	Actuator (air - spring, air - air)	

## 11 Classification

## 11.1 Structure of Order Number



#### **Product name**

4x3x xxx xxx-xxx				
Product name	Pos. 0	Pos. 2		
Three way ball valve	4	3		

e.g. Type 4231 - Three way ball cock pneumatic operation, air open - spring close (NC)


#### Kind of actuators

4 <mark>x</mark> 3x xxx xxx-xxx			
Kind of actuation	Pos. 1		
Manual operation	0		
Pneumatic actuator (air / air)	1		
Pneumatic actuator (air / spring)	2		

#### **Connection variants**

4x3 <mark>x</mark> xxx xxx-xxx				
Combination of flange connection	Pos. 3	Pos. 7	Pos. 8	Pos. 9
(G-G-G) 3 x Male part	1			
(K/M-G-G) Liner/nut - 2x Male part	2			
(FI-FI-FI) 3x Small flange PN10	3			

## Valve size



## Sealing material / construction modification

4x3x xxx xxx-xxx	
Sealing material - in product contact:	EPDM; NBR; FKM
Construction modification:	Filling element PTFE; heatable; rinsable;
	L-ball; T-ball

## Separator

4x3x xxx xxx <mark>-</mark> xxxx	Pos. 10
Separator	-

## Control system, External surface

4x3x xxx xxx-xxxx				
Control system and position indicator	Pos. 11	Pos. 12	Pos. 13	Pos. 14
Control head SPS (old version)	5	х	Х	
Control head ASi-Bus (old version)	6	х	Х	
Control head KI-Top SPS	K	5	Х	х
Control head KI-Top ASi-Bus	K	6	Х	Х

External surface	Pos. 11	Pos. 12	Pos. 13	Pos. 14
Valve with position indication	0	2	0	
External surface: AISI304, blank				
Valve with position indication	0	4	0	
External surface: AISI316L, blank				
Valve with position indication	0	2	1	
External surface AISI304, E-polished				
Valve with position indication	0	4	1	
External surface AISI316L, E-polished				
Valve with position indication	0	2	2	
External surface: AISI304, mat glass-bead blasted				
Valve with position indication	0	4	2	
External surface: AISI316Lat glass-bead blasted				

## 12 Appendix

## 12.1 Declaration of incorporation



#### **Declaration of incorporation**

Translation of the original

Manufacturer / authorised representative: KIESELMANN GmbH

Paul-Kieselmann-Str. 4-10 75438 Knittlingen

Germany

Authorised representative:

(for compiling technical documents)

Achim Kauselmann

Paul-Kieselmann-Str. 4-10

75438 Knittlingen

Germany

Product name Function

pneum. Lift actuators
pneum. Rotary actuators
Ball valves
Stroke movement
Rotary movement
Media cutoff

Butterfly valves Media cutoff
Single seat valves Media cutoff

Flow control valves Control of liquefied media
Throttle valve Control of liquefied media
Overflow valve Definition of fluid pressure

Double seat valve

Bellow valves
Sampling valves
Two way valves

Media separation
Sampling of liquids
Sampling of liquids
Media cutoff

Tankdome fitting Prevention of overpressure and vacuum, Tank cleaning

Safety valve Prevention of overpressure

The manufacturer hereby states that the above product is considered as an incomplete machine in the sense defined in the Directive 2006/42/EC on Machinery. The above product is exclusively intended to be installed into a machine or an incomplete machine. The said product does not yet conform to all the relevant requirements defined in the Directive on Machinery referred to above for this reason.

The specific technical documents listed in Appendix VII, Part B, have been prepared. The Authorized Agent empowered to compile technical documents may submit the relevant documents if such a request has been properly justified.

Commissioning of an incomplete machine must not only carried out if it has been determined that the respective machine into which the incomplete machine is to be installed conforms to the regulations set out in the Directive on Machinery referred to above.

The above product conforms to the requirements of the directives and harmonized standards specified below:

- Directive 2014/68/EU
- · DIN EN ISO 12100 Safety of machinery

Knittlingen, 21.07.2017

i.V. Uwe Heisswolf Head of Development